

# Riverside Energy Park

---

## Preliminary Environmental Information Report

---

APPENDIX:

# D.2

PLANNING INSPECTORATE REFERENCE NUMBER:  
**EN010093**

---

**NOISE AND VIBRATION  
GLOSSARY**

---

June 2018 | Revision 0

---

Planning Act 2008 | Infrastructure Planning (Applications: Prescribed Forms and Procedure) Regulations 2009

## D.2– Glossary

Parameter	Description
Ambient Noise Level	The totally encompassing sound in a given situation at a given time, usually composed of a sound from many sources both distant and near ( $L_{Aeq,T}$ ).
Daytime	The period 07:00-23:00 hours.
Decibel (dB)	A scale for comparing the ratios of two quantities, including sound pressure and sound power. The difference in level between two sounds $s_1$ and $s_2$ is given by $20 \log_{10} (s_1/s_2)$ . The decibel can also be used to measure absolute quantities by specifying a reference value that fixes one point on the scale. For sound pressure, the reference value is $20 \mu\text{Pa}$ . The threshold of normal hearing is in the region of 0 dB and 140 dB is the threshold of pain. A change of 1 dB is only perceptible under controlled conditions.
dB(A), $L_{Ax}$	Decibels measured on a sound level meter incorporating a frequency weighting (A weighting) which differentiates between sounds of different frequency (pitch) in a similar way to the human ear. Measurements in dB(A) broadly agree with people's assessment of loudness. A change of 3 dB(A) is the minimum perceptible under normal conditions, and a change of 10 dB(A) corresponds roughly to halving or doubling the loudness of a sound. The background noise in a living room may be about 30 dB(A); normal conversation about 60 dB(A) at 1 metre; heavy road traffic about 80 dB(A) at 10 metres; the level near a pneumatic drill about 100 dB(A).
Fast Time Weighting	Setting on sound level meter, denoted by a subscript F that determines the speed at which the instrument responds to changes in the amplitude of any measured signal. The fast time weighting can lead to higher values than the slow time weighting when rapidly changing signals are measured. The average time constant for the fast response setting is 0.125 (1/8) seconds.
Free-field	Sound pressure level measured outside, far away from reflecting surfaces (except the ground), usually taken to mean at least 3.5 metres
Façade noise	Sound pressure level measured at a distance of 1 metre in front of a large sound reflecting object such as a building façade.
Insertion Loss	Insertion loss is the difference in sound pressure level at a single fixed position before and after a noise control element (e.g. enclosure, barrier etc) is installed.
$L_{AE}$ or SEL	A noise level which, if maintained for a period of 1 second, would cause the same A-weighted sound energy to be received as is actually received from a given noise event.
$L_{Aeq,T}$	A noise level index called the equivalent continuous noise level over the time period T. This is the level of a notional steady sound that would contain the same amount of sound energy as the actual, possibly fluctuating, sound that was recorded.
$L_{max,T}$	A noise level index defined as the maximum noise level recorded during a noise event with a period T. $L_{max}$ is sometimes used for the

	assessment of occasional loud noises, which may have little effect on the overall $L_{eq}$ noise level but will still affect the noise environment. Unless described otherwise, it is measured using the 'fast' sound level meter response.
$L_{10,T}$	A noise level index. The noise level exceeded for 10 % of the time over the period T. $L_{10}$ can be considered to be the "average maximum" noise level. Generally used to describe road traffic noise. $L_{A10,18h}$ is the A – weighted arithmetic average of the 18 hourly $L_{A10,1h}$ values from 06:00-24:00.
$L_{90,T}$ or Background Noise Level	A noise level index. The noise level exceeded for 90 % of the time over the period T. $L_{90}$ can be considered to be the "average minimum" noise level and is often used to describe the background noise.
LOAEL	Lowest Observed Adverse Effect Level. This is the noise level above which adverse effects on health and quality of life can be detected.
Night-time	The period 23:00-07:00 hours.
NOEL	No Observed Effect Level. This is the level below which no effect can be detected. In simple terms, below this level, there is no detectable effect on health and quality of life due to the noise.
Noise Indices	Noise levels usually fluctuate over time, so it is often necessary to consider an average or statistical noise level. This can be done in several ways, so a number of different noise indices have been defined, according to how the averaging or statistics are carried out.
SOAEL	Significant Observed Adverse Effect Level. This is the level above which significant adverse effects on health and quality of life occur.
Sound Pressure	Sound, or sound pressure, is a fluctuation in air pressure over the static ambient pressure.
Sound Pressure Level, $L_p$	The sound pressure level, $L_p$ is the sound pressure relative to a standard reference pressure of 20 $\mu\text{Pa}$ ( $20 \times 10^{-6}$ Pascals) on a decibel scale. Pascal is a unit of pressure used to quantify internal pressure.
Specific Noise Level	The noise source under investigation for assessing the likelihood of complaints, measured as and $L_{Aeq,T}$
Rating Noise Level	The specific noise source plus any adjustment for the characteristic features of the noise, denoted by $L_{Ar,T}$ .